



## Meter Socket Adapter with Coupler Kit

The Adapter Kit is designed to work with the UEA-200 Standard Meter Socket Adapter. It can be purchased as an assembled finish good with attached enclosure or as a kit that you can assemble.

The specifications for the optional enclosure vary based on application needs (hinged door enclosure shown). The Adapter Kit with Coupler can be customized to meet your requirements. Contact the factory for all available options.

### UEA-200 Specs

Meets all ANSI and UL dimension requirements for meter sockets

Listed 200 amp continuous (250 Max in 200A meter socket)

260 amp continuous (325A Max in 320A meter socket)

Fiberglass reinforced polycarbonate

UL 94-5VA flame rating

UV stabilized plastic

Up to 10 jaw capability (4 Jaw Shown)

For 1S, 2S, 3S, 4S, 5S, 12S and 15S Meter Sockets

External ground connection

Wiring pass thru hole

Adapted or machined to your specifications

3 o'clock jaw position for load management

Buss bar .25 Slide or threaded connector

Single or Three phase Configurations Available



Couplers may also be purchased individually. Square and Round available.



### Example Kit with Meter Adapter

#### Dimensions

Internal: 1.1" x 1.1"

Outer: 1.5" x 1.5" x 1.3"L

Drawings Available

Container Opening: 1" to 1<sup>1</sup>/<sub>16</sub>" hole

#### Example Kit Includes:

Qty 1 ANSI/UL Listed Meter Housing  
200Amp/250Max

Qty 4 #8 Washers

Qty 4 Bolts 8-32x2 PPH

Qty 4 Nuts 8-32 w/ tooth lockwasher

Qty 2 Neoprene Gaskets

Qty 1 Coupler, 10% glass filled polycarbonate