

Also Available As OEM Products

## Specification & Features

UV Stabilized Plastic
Flame Rating: 5VA/V-0 (Grey), HB (colors)
Polycarbonate (Fiberglass Reinforced Grey)
Fits Ring or Ringless Style Meter Sockets ( <a href="#">More Information</a> )
Listed to UL414
Meets all ANSI and UL Dimension Requirements for Meter Sockets
Listed for 200 AMP Continuous (250A Max in 200A Meter Socket)
Listed for 260 AMP Continuous (325A Max in 320A Meter Socket)
RotoLock Mechanism Option Available ( <a href="#">More Information</a> )



The AE Products Meter Socket Adapters may be used to convert meter sockets to test or control applications. Meter Socket Adapters can be used to easily convert a Ringless style meter socket to a Ring Style. These adapters can be custom machined to your specifications.

### Additional Options Available:

- Surge Protection
- Wire Pass Through Hole
- Up to 10 Jaw Capacity
- External Ground Connection
- Polycarbonate Window with LED Holder
- Bus Bar 0.25 Slide or Threaded Connector
- 3 O'Clock Jaw Position Available for Load Management

## Model Number Configuration

**MSA - LP - 02S - 01 / \_\_\_\_\_ - \_\_\_\_\_**

Standard Size	Conversion	Color	Options (Multiple Options Allowed)	
LP - Low Profile	<b>Meter Form</b>	01 - Gray	<b>Diagnostics</b>	<b>Ground</b>
SP - Standard Profile	01S - 1S	02 - Black	LEN - Lens/Window	GND - Meter Ground (Strap)
	02S - 2S	03 - Blue	LNG - Line Side Status (Green)	<b>Jaw Blade Configurations</b>
	03S - 3S	04 - Clear	LNR - Line Side Status (Red)	JB3 - 3 o'clock position
	04S - 4S	05 - Fern Green	LDG - Line Side Status (Green)	JB6 - 6 o'clock position
	05S - 5S	06 - Fluor Green	LDR - Line Side Status (Red)	JB9 - 9 o'clock position
	07S - 7S	07 - Orange	PWR - Power On (Red)	<b>Protective Shield</b>
	12S - 12S	08 - Red	<b>RotoLock Mechanism</b>	SHD - Shield
	13S - 13S	09 - Pink	RL - RotoLock Mechanism	<b>Surge Protection</b>
	14S - 14S	10 - Off White	(Available on SP Version ONLY)	SP1 - Single MOV Block
	15S - 15S	11 - Yellow		SP2 - Dual MOV Block
	16S - 16S			
	17S - 17S			
	24S - 24S			
	25S - 25S			
	35S - 35S			
	45S - 45S			

Note: You may add additional options as needed by extending the model number